

## Distributed Systems

### 03r. Python Web Services Programming Tutorial

Paul Krzyzanowski  
TA: David Domingo  
Rutgers University  
Fall 2018

September 20, 2018

1

## From Web Browsing to Web Services

- Web browser:
  - Dominant model for user interaction on the Internet
- Not good for programmatic access to data or manipulating data
  - UI is a major component of the content
  - *Site scraping* is a pain!

September 20, 2018

2

## Web Services

- We wanted:
  - Remotely hosted services – that programs can use
  - Machine-to-machine communication
- Problems
  - Web pages are content-focused
  - Traditional RPC solutions usually used a range of ports
    - And we need more than just RPC sometimes
  - Many RPC systems didn't work well across languages
  - Firewalls restrict ports & may inspect the protocol
  - No support for load balancing

September 20, 2018

3

## Web Services

- Set of protocols by which services can be published, discovered, and used in a technology neutral form
  - Language & architecture independent
- Applications will typically invoke multiple remote services
  - **Service Oriented Architecture (SOA)**
  - SOA = Programming model
- General principles
  - Payloads are text (XML or JSON)
    - Technology-neutral
  - HTTP used for transport
    - Use existing infrastructure: web servers, firewalls, load-balancers

September 20, 2018

4

## REST

- REST stands for **RE**presentational **S**tate **T**ransfer
- REST was first introduced by Roy Fielding in year 2000
- REST is a web standards based architecture
  - Uses HTTP Protocol for data communication
  - Resource-oriented
    - every component is a resource
    - a resource is accessed by a common interface using HTTP standard methods

September 20, 2018

5

## REST

- REST Server
  - simply provides access to resources
- REST client
  - accesses and presents the resources
- REST resources
  - each resource is identified by URIs/ Global IDs
  - representations of a resource
    - Text, JSON and XML
    - JSON is now the most popular format

September 20, 2018

6

## RESTful Web Services

- A web service is:
  - A collection of open protocols
  - Standards used for exchanging data between applications or systems
  - Interoperability between different languages (Java and Python) or platforms (Windows and Linux)
- Web services based on REST Architecture are known as RESTful Web Services
  - Use HTTP methods to implement the concept of REST architecture
  - URI (Uniform Resource Identifier) to define a RESTful service
  - Resources representation: JSON

September 20, 2018

7

## Everything Is a Resource

- Any interaction of a RESTful API is an interaction with a resource.
- Resources are sources of information, typically documents or services.
- A user can be thought of as resource and thus has an URL such as in the case of **GitHub**:

```
https://api.github.com/users/lrei
```

September 20, 2018

8

## Everything Is a Resource

- Resources can have different **representations**. The above mentioned user has the following JSON representation (partial document):

```
{
  "login": "lrei",
  "created_at": "2008-11-21T14:48:42Z",
  "name": "Luis Rei",
  "email": "me@luisrei.com",
  "id": 35857,
  "blog": "http://luisrei.com"
}
```

September 20, 2018

9

## Everything Is a Resource

- Resources are Nouns
  - If I want to delete a post whose ID is 233:

```
http://api.example.com/posts/delete/233/
```

- The correct way:

Send a **DELETE** HTTP request to the URL:

```
http://api.example.com/posts/233/
```

September 20, 2018

10

## HTTP Methods

- The following HTTP methods are most commonly used in a REST based architecture.
- **GET** – Provides a read only access to a resource.
- **PUT** – Used to create a new resource.
- **DELETE** – Used to remove a resource.
- **POST** – Used to update an existing resource or create a new resource.
- **OPTIONS** – Used to get the supported operations on a resource.

September 20, 2018

11

## Implementing RESTful Web APIs with Python & Flask

September 20, 2018

12

## Flask

- Flask is a microframework for Python based on Werkzeug, a WSGI utility library
- Flask is a good choice for a REST API because it is:
  - Written in Python
  - Simple to use
  - Flexible
  - Multiple good deployment options
  - RESTful request dispatching

September 20, 2018

13

## RESTful Web APIs with Python & Flask

- To install (if not installed):

```
$ (sudo) pip install flask
```

- We can use the `curl` command to make test requests.
  - `curl` is a command that lets you transfer data to or from a server using several protocols, most commonly HTTP

See <https://curl.haxx.se>

*Note: the iLab systems already have flask and python installed*

September 20, 2018

14

## RESTful Web APIs with Python & Flask

- Let's begin by making a complete app that responds to requests at the root, `/articles` and `/articles/:id`.

```
from flask import Flask, url_for
app = Flask(__name__)

@app.route("/")
def api_root():
    return 'Welcome!\n'

@app.route("/articles")
def api_articles():
    return 'List of ' + url_for('api_articles') + '\n'
...
```

September 20, 2018

15

## RESTful Web APIs with Python & Flask

- Let's begin by making a complete app that responds to requests at the root, `/articles` and `/articles/:id`.

```
...
@app.route("/articles/<articleid>")
def api_article(articleid):
    return 'You are reading ' + articleid + '\n'

if __name__ == '__main__':
    app.run()
```

September 20, 2018

16

## RESTful Web APIs with Python & Flask

- You can use `curl` to make the requests using:

```
$ curl http://127.0.0.1:5000/
```

- The responses will be, respectively,

```
$ curl http://127.0.0.1:5000/
GET /
Welcome
```

```
$ curl http://127.0.0.1:5000/articles
GET /articles
List of /articles
```

```
$ curl http://127.0.0.1:5000/articles/123
GET /articles/123
You are reading 123
```

September 20, 2018

17

## GET Parameters

- Let's begin by making a complete app that responds to requests at `/hello` and handles an optional GET parameter

```
from flask import request

@app.route("/hello")
def api_hello():
    if 'name' in request.args:
        return 'Hello ' + request.args['name'] + '\n'
    else:
        return 'Hello John!\n'

if __name__ == '__main__':
    app.run()
```

September 20, 2018

18

## GET Parameters

- The server will reply in the following manner:

```
$ curl http://127.0.0.1:5000/hello
GET /hello
Hello John

$ curl http://127.0.0.1:5000/hello?name=Peter
GET /hello?name=Peter
Hello Peter
```

September 20, 2018

19

## Request Methods (HTTP Verbs)

- Let's modify the to handle different HTTP verbs:

```
@app.route('/echo', methods = ['GET', 'POST', 'PUT', 'DELETE'])
def api_echo():
    if request.method == 'GET':
        return "ECHO: GET\n"

    elif request.method == 'POST':
        return "ECHO: POST\n"

    elif request.method == 'PUT':
        return "ECHO: PUT\n"

    elif request.method == 'DELETE':
        return "ECHO: DELETE\n"
```

September 20, 2018

20

## Request Methods (HTTP Verbs)

- To curl the -X option can be used to specify the request type:

```
$ curl -X POST http://127.0.0.1:5000/echo
```

- The replies to the different request methods will be:

```
GET /echo
ECHO: GET

POST /echo
ECHO: POST

...
```

September 20, 2018

21

## Request Data & Headers

- Usually POST is accompanied by data
  - That data can be in one of multiple formats: plain text, JSON, XML, your own data format, a binary file
- Accessing the HTTP headers is done using the `request.headers` dictionary ("dictionary-like object") and the request data using the `request.data` string
- If the mimetype is `application/json`, `request.json` will contain the parsed JSON

September 20, 2018

22

## Request Data & Headers

- Usually POST is accompanied by data
  - That data can be in one of multiple formats
    - plain text, JSON, XML, your own data format, a binary file

```
from flask import json

@app.route('/messages', methods = ['POST'])
def api_message():
    if request.headers['Content-Type'] == 'text/plain':
        return "Text Message: " + request.data + '\n'

    elif request.headers['Content-Type'] == 'application/json':
        return json.dumps(request.json)

    else:
        return "415 Unsupported Media Type :)"
```

September 20, 2018

23

## Request Data & Headers

- To specify the content type with curl:
 

```
$ curl -H "Content-type: application/json" -X POST \
  http://127.0.0.1:5000/messages -d '{"message": "Hello Data"}'
```
- The replies to the different content types will be:

```
POST /messages "Hello Data"
Content-type: text/plain
Text Message: Hello Data

POST /messages {"message": "Hello Data"}
Content-type: application/json
{"message": "Hello Data"}
```

September 20, 2018

24

## Responses

- Responses are handled by Flask's **Response class**:

```
from flask import Response

@app.route('/hello', methods = ['GET'])
def api_hello():
    data = { 'hello': 'world', 'number': 3 }
    js = json.dumps(data)
    resp = Response(js, status=200, mimetype='application/json')
    return resp
```

September 20, 2018

25

## Responses

- To view the response HTTP headers using curl, specify the **-i** option:

```
$ curl -i http://127.0.0.1:5000/hello
```

- The response returned by the server, with headers included, will be:

```
GET /hello
HTTP/1.0 200 OK
Content-Type: application/json
Content-Length: <...>
Server: <...>
Date: <...>
{"hello": "world", "number": 3}
```

September 20, 2018

26

## Status Codes & Errors

- 200** is the default status code reply for **GET** requests in both of these examples
- There are certain cases where overriding the defaults is necessary: error handling

September 20, 2018

27

## Status Codes & Errors

```
@app.errorhandler(404)
def not_found(error=None):
    message = { 'status': 404, 'message': 'Not Found!' + request.url }
    resp = jsonify(message)
    resp.status_code = 404
    return resp

@app.route('/users/<userid>', methods = ['GET'])
def api_users(userid):
    users = { '1': 'john', '2': 'steve', '3': 'bill' }
    if userid in users:
        return jsonify({ 'userid': users[userid] })
    else:
        return not_found()
```

September 20, 2018

28

## Status Codes & Errors

- This produces:

```
GET /users/2
HTTP/1.0 200 OK { "2": "steve" }

GET /users/4
HTTP/1.0 404 NOT FOUND
{
  "status": 404,
  "message": "Not Found: http://127.0.0.1:5000/users/4"
}
```

September 20, 2018

29

## Other Useful Links

- iLab: <https://www.cs.rutgers.edu/resources/instructional-lab>
- JSON: <http://www.json.org/>
- Flask Framework: <http://flask.pocoo.org/>
- Flask Quick Start: <http://flask.pocoo.org/docs/0.12/quickstart/>
- Implementing a RESTful Web API with Python & Flask: <http://blog.luisrei.com/articles/flaskrest.html>

September 20, 2018

30

